

## General Description

The Sanrise SRC60R030FBS is a high voltage power MOSFET, fabricated using advanced super junction technology. The resulting device has extremely low on resistance, low gate charge and fast switching time, making it especially suitable for applications which require superior power density and outstanding efficiency.

The SRC60R030FBS break down voltage is 600V and it has a high rugged avalanche characteristics.

The SRC60R030FBS is available in TO-247 package.

## Features

- Ultra Low  $R_{DS(ON)} = 30m\Omega @ V_{GS} = 10V$ .
- $V_{ds}@T_{jmax}=650V$ .
- Ultra Low Gate Charge,  $Q_g=187nC$  typ.
- Fast switching capability
- Robust design with better EAS performance
- Low  $Q_{rr}$
- Non-automotive Qualified
- Ultra-fast body diode

## Symbol

## Application

- High Performance Application
- High Power Application
- EV Charger

## Ordering Information





Figure 1 Symbol of SRC60R030FBS

## Package Type




Figure 2 Package Type of SRC60R030FBS

Package	Part Number	Marking ID	Packing Type
TO-247	SRC60R030FBST-G	SRC60R030FBSTG	Tube

**Absolute Maximum Ratings**<sup>Note 1</sup>

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		$V_{DSS}$	600	V
Gate-Source Voltage (static)		$V_{GSS}$	±20	V
Gate-Source Voltage (dynamic), AC (f>1 Hz)		$V_{GSS}$	±30	V
Power Dissipation( $T_C=25^{\circ}C, TO-247$ )		$P_{tot}$	500	W
Continuous Drain Current	$T_C=25^{\circ}C$	$I_D$	91	A
	$T_C=100^{\circ}C$		57	
	$T_C=125^{\circ}C$		41	
Pulsed Drain Current (Note 2)		$I_{DM}$	273	A
Avalanche Energy, Single Pulse (Note 3)		$E_{AS}$	200	mJ
Avalanche Energy, Single Pulse (Note 4)		$E_{AS}$	1889	mJ
Avalanche Energy, Repetitive (Note 2)		$E_{AR}$	1.0	mJ
Avalanche Current, Repetitive (Note 2)		$I_{AR}$	6.4	A
Continuous Diode Forward Current		$I_S$	91	A
Diode Pulse Current		$I_{S,PULSE}$	273	A
MOSFET dv/dt Ruggedness, $V_{DS} \leq 480V$		dv/dt	120	V/ns
Reverse Diode dv/dt, $V_{DS} \leq 480V, I_{SD} \leq I_D$		dv/dt	50	V/ns
Operating Junction Temperature		$T_J$	150	°C
Storage Temperature		$T_{STG}$	-55 to 150	°C
Lead Temperature (Soldering, 10 sec)		$T_{LEAD}$	260	°C

Note:

1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
2. Repetitive Rating: Pulse width limited by maximum junction temperature
3.  $I_{AS} = 6.4A, V_{DD} = 60V, R_G = 25\Omega$ , Starting  $T_J = 25^{\circ}C$ . Finish goods test condition.
4.  $I_{AS} = 19.4A, V_{DD} = 60V, R_G = 25\Omega$ , Starting  $T_J = 25^{\circ}C$ . Typical Eas.

**Thermal characteristics**

Parameter		Symbol	Min	Typ	Max	Unit
Thermal resistance, Junction-to-Case	TO-247	$R_{thJC}$			0.25	°C /W
Thermal resistance, Junction-to-Ambient	TO-247	$R_{thJA}$			60	°C /W

**Electrical Characteristics**
 $T_J = 25^\circ\text{C}$ , unless otherwise specified.

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Statistic Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	600			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=600V, V_{GS}=0V$			10	$\mu A$
Gate-Body Leakage Current	Forward	$I_{GSSF}, V_{GS}=20V, V_{DS}=0V$			100	nA
	Reverse	$I_{GSSR}, V_{GS}=-20V, V_{DS}=0V$			-100	
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=2.2mA$	3.0	4.0	5.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=34A$		23.7	30	$m\Omega$
Gate Resistance	$R_G$	$f=1MHz, \text{Open Drain}$		1.0		$\Omega$
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{ISS}$	$V_{DS}=400V,$		8.6		nF
Output Capacitance	$C_{OSS}$	$V_{GS}=0V, f=100kHz$		165		pF
Effective output capacitance, energy related <sup>NOTE5</sup>	$C_{O(er)}$	$V_{GS}=0V,$ $V_{DS}=0\dots 400V$		222		pF
Effective output capacitance, time related <sup>NOTE6</sup>	$C_{O(tr)}$			1354		
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=400V, I_D=34A$ $R_G=3\Omega, V_{GS}=12V$		66		ns
Rise Time	$t_r$			39		
Turn-off Delay Time	$t_{d(off)}$			103		
Fall Time	$t_f$			10		
<b>Gate Charge Characteristics</b>						
Gate to Source Charge	$Q_{gs}$	$V_{DD}=400V, I_D=34A$ $V_{GS}=0 \text{ to } 10V$		70		nC
Gate to Drain Charge	$Q_{gd}$			69.5		
Gate Charge Total	$Q_g$			187		
Gate Plateau Voltage	$V_{plateau}$			6.9		V
<b>Reverse Diode Characteristics</b>						
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V, I_{SD}=34A$		0.9	1.1	V
Reverse Recovery Time	$t_{rr}$	$V_R=400V, I_F=34A$ $dI_F/dt=100A/\mu s$		197		ns
Reverse Recovery Charge	$Q_{rr}$			2.4		$\mu C$
Peak Reverse Recovery Current	$I_{rrm}$			20		A

Note:

- $C_{O(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 480V
- $C_{O(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 480V



TM

**Sanrise Tech**  
**尚阳通**

Shenzhen Sanrise Technology Co., LTD

<http://www.sanrise-tech.com>**IMPORTANT NOTICE**

Shenzhen Sanrise Technology Co., LTD reserves the right to make changes without further notice to any products or specifications herein. Shenzhen Sanrise Technology Co., LTD does not assume any responsibility for use of any its products for any particular purpose, nor does Shenzhen Sanrise Technology Co., LTD assume any liability arising out of the application or use of any its products or circuits. Shenzhen Sanrise Technology Co., LTD does not convey any license under its patent rights or other rights nor the rights of others.

**Main Site:****- Headquarter**

Shenzhen Sanrise Technology Co., LTD.  
A1206, Skyworth building, No. 008, gaoxinnan 1st Road,  
Gaoxin District, Yuehai street,, Nanshan District, ShenZhen,  
P.R.China  
Tel: +86-755-22953335  
Fax: +86-755-22916878

**- Shanghai Office**

Shenzhen Sanrise Technology Co., LTD  
Rm.401, Building B, No. 666, Zhangheng Road,  
Zhangjiang Hi-Tech Park, Shanghai, P.R.China  
Tel: +86-21-68825918